

输出交流电抗器 Output AC Reactor

380V输出交流电抗器(1%压降)选型表
380v Output AC reactor (1% drop) selection table

电抗器型号 Reactor Type	图号 Picture NO.	功率 Power	额定 电流 Rated Current (A)	绝缘 等级 Insulation Class	重量 (kg) Weight (kg)	尺寸 Dimension(±5mm)										铜排尺寸 Terminal Size								
						D	D1	D2	W	W1	W2	H	H1	H2	E	A*B	A	A1	B	T	C			
OCL-0005-EISC-E1M4	图 A	1.5	5	F	2.48	110	91	105	/	65	84	130	/	/	/	6×11								
OCL-0007-EISC-E1M0		2.2	7	F	2.54	110	91	105	/	65	84	130	/	/	/	6×11								
OCL-0010-EISC-EM70		3.7	10	F	2.67	110	91	105	/	65	84	130	/	/	/	6×11								
OCL-0015-EISC-EM47	Picture A	5.5	15	F	3.45	155	95	148	/	61	76	130	/	/	/	6×15								
OCL-0020-EISC-EM35		7.5	20	F	3.25	155	95	148	130	61	76	150	/	/	/	6×15								
OCL-0030-EISC-EM23	图 B	11	30	F	5.5	155	95	148	135	80	95	130	/	/	/	6×15			KF 8-5					
OCL-0040-EISC-EM18		15	40	F	5.5	155	95	148	135	80	95	130	/	/	/	6×15			KF 8-5					
OCL-0050-EISC-EM14		18.5	50	F	5.6	155	95	148	135	72	95	130	/	/	/	6×15			KF 14-6					
OCL-0060-EISC-EM12		22	60	F	5.8	195	120	188	130	72	92	165	/	/	/	8.5×20			KF 22-6					
OCL-0080-EISC-E87U		30	80	F	6.0	195	120	188	130	72	92	165	75	40	68	8.5×20	20	/	10	4		φ9		
OCL-0090-EISC-E78U		37	90	F	6.0	195	120	188	130	72	92	165	75	40	68	8.5×20	20	/	10	4		φ9		
OCL-0120-EISC-E58U		45	120	F	9.6	195	120	188	135	92	112	165	75	40	78	8.5×20	20	/	10	4		φ9		
备注: 公差 D:max D1:±1 D2:±1 W:max W1:±2 W2:±2 H:max H1:±5 H2:±5 E:±10,其余未注公差±0.5mm.																								
OCL-0150-EISH-E47U	图 C	55	150	F	15	250	182	81	170	76	113	230	140	42	97	11×18	25	/	13	5		φ11		
OCL-0200-EISH-E35U		75	200	F	17.3	250	182	81	175	96	123	230	140	42	102	11×18	25	/	13	5		φ11		
OCL-0250-EISH-E28U		110	250	F	17.8	250	182	81	175	96	123	230	140	42	102	11×18	25	/	13	5		φ11		
OCL-0290-EISH-E24U		132	290	F	24.7	290	214	95	190	100	127	250	150	45	107	11×18	30	/	15	5		φ12		
OCL-0330-EISH-E21U		160	330	F	26	290	214	95	190	100	132	250	155	45	110	11×18	30	/	15	5		φ12		
OCL-0390-EISH-E18U		185	390	F	26.5	290	214	95	190	112	132	250	155	45	110	11×18	30	/	15	5		φ12		
OCL-0490-EISH-E14U		220	490	F	36.6	320	243	106	220	122	143	320	190	52	132	12×20	50	22	23	8		2-φ12		
OCL-0530-EISH-E13U		240	530	F	36.6	320	243	106	220	122	143	320	190	52	132	12×20	50	22	23	8		2-φ12		
OCL-0600-EISH-E12U		280	600	F	43.5	320	243	106	240	137	158	320	195	50	140	12×20	50	22	23	8		2-φ12		
OCL-0660-EISH-E11U		300	660	F	44	320	243	106	240	137	158	320	195	50	140	12×20	50	22	23	8		2-φ12		
OCL-0800-EISH-E8U7		380	800	F	60.8	385	260	123	250	175	198	395	230	70	137	12×20	50	22	23	8		2-φ12		
OCL-1000-EISH-E7U0		450	1000	F	61.5	385	260	123	250	175	198	395	230	70	137	12×20	50	22	23	8		2-φ12		
OCL-1200-EISH-E5U8		550	1250	F	89	395	275	130	325	175	198	435	280	65	207	12×20	60	26	27	12		4-φ12		
OCL-1600-EISH-E4U3	630	1600	F	92	395	275	130	325	175	198	435	280	65	207	12×20	60	26	27	12		4-φ12			

备注:(1) : Picture C公差 D:max D1:±1 D2:±5 W:max W1:±2 W2:±2 H:max H1:±5 H2:±5 E:±10,其余未注公差±0.5mm.
Picture D公差 D:max D1:±2 D2:±5 W:max W1:±1 W2:±1 H:max H1:±5 H2:±5 E:±10,其余未注公差±0.5mm.
(2) : 以上型号为我司标准品, 1600A~3000A以下可以根据客户要求定制。
(3) : H级产品可以根据客户要求定制。

(以上参数仅供参考, 选型时请咨询我司业务)

产品尺寸图 (Product Size)

